IJTRET "Voice of Innovative Minds"

doi.org/10.54473/IJTRET.2023.7203
International Journal of Trendy Research in Engineering and Technology
Volume 7 Issue 2 April 2023
ISSN NO 2582-0958

HEAT CONDUCTED THROUGH FINS OF VARYING CROSS-SECTIONS

[1]Rohit Gupta*, [2]Neeraj Pandita, [2]Inderdeep Singh
[1]Lecturer,Department of Applied Sciences, [2]Assistant Professor, Department of Mechanical engineering
Yogananda College of Engineering and Technology, Jammu, J&K, INDIA
*Corresponding author: guptarohit565@gmail.com

Received 09 March 2023 Received Revised Form 12 March 2023 Accepted 13 March 2023
Available Online 16 March 2023

ABSTRACT

The conduction of heat takes place through the fins or spines from particle to particle due to a temperature gradient in the direction of decreasing temperature. Heat is not lost equally by each element of the fin but is lost mostly near the base of the fin. Thus there would be a waste of the material if a uniform fin is used. These aspects demand the construction of fins of varying cross-sections like triangular fin, hyperbolic fin, and parabolic fin. The paper analyzes a triangular fin and a parabolic fin to find the rate of conduction of heat through them via Laplace Transform means. The results obtained are the same as obtained with other methods.

Index terms: Triangular fin, Parabolic fin, Laplace Transform.

I INTRODUCTION

The conduction of heat takes place through the fins or spines from particle to particle due to a temperature gradient in the direction of decreasing temperature [1, 2]. Fins or spines are the extended surfaces that are mostly used in devices that exchange heat [3] like computer central processing units, power plants, radiators, heat sinks, etc. The paper analyzes a triangular fin and a parabolic fin to find the rate of conduction of heat through them via Laplace Transform means. Laplace Transform means comes out to be a very effective tool to find the temperature distribution along a triangular fin, and a parabolic fin and hence the rate of conduction of heat through them.

The Laplace transform [4, 5] of a function $y(x)$ is defined as $L[y(x)] = \int_0^\infty e^{-px}\, y(x)\, dx = Y(p)$, provided that the integral is convergent for some value of the real or complex parameter p. The Laplace transform of derivatives [5, 6] of $y(x)$ is given by

$$L\{y'(x)\} = pY(p) - y(0),$$

$$L\{y''(x)\} = p^2H(p) - \mathrm{p}y(0) - y'(0),$$

and so on.

II MATERIAL AND METHOD

Case I: Triangular Fin

The differential equation for analyzing a triangular fin [6] (assuming that heat flow pertains to one - dimensional conduction of heat) is given by

$$\theta''(x) + \frac{1}{x}\theta'(x) - \frac{D^2}{x}\theta(x) = 0 \ldots\ldots (1),$$

$where\ D = \sqrt{\frac{2hL}{tk}}$, L is the length of the fin between the base at x = L and the tip at x = 0, t is the thickness of the fin which increases uniformly from zero at the tip to t at the base, k is thermal conductivity, h is the coefficient of transfer of heat by convection, $\theta(x) = T(x) - T_s$, T_s is the temperature of the environment of the fin.

Multiplying both sides of (1) by x, we get

$$x\,\theta''(x) + \theta'(x) - D^2\theta(x) = 0 \ldots\ldots (2)$$

The Laplace transform [7, 8] of (2) gives

$$-\frac{d}{dp}[\,p^2\theta(p) - p\theta(0) - \theta'(0)] + p\,\theta(p) - \theta(0) - D^2\theta(p) = 0 \ldots\ldots. (3)$$

Put $\theta(0) = b \; and \; \theta'(0) = a$, and by simplifying and rearranging (3), we get

$$\frac{\theta'(p)}{\theta(p)} = -[\frac{1}{p} + \frac{D^2}{p^2}] \ldots\ldots (4)$$

Integrating both sides of (4) w.r.t. p and simplifying, we get

$$\log_e \theta(p) = -[\log_e p - D^2\frac{1}{p} - \log_e c] \ldots.. (5)$$

Simplifying (5), we get

$$p\,\theta(p) = ce^{(D^2\frac{1}{p})}$$

Expanding the exponential term, we get

$$p\,\theta(p) = \left[1 + D^2\frac{1}{p} + \frac{\left(D^2\frac{1}{p}\right)^2}{2!} + \frac{\left(D^2\frac{1}{p}\right)^3}{3!} + \frac{\left(D^2\frac{1}{p}\right)^4}{4!} \ldots\ldots\right]$$

$$or \;\; \theta(p) = \left[\frac{1}{p} + D^2\frac{1}{p^2} + \frac{D^4}{2!}\frac{1}{p^3} + \frac{D^6}{3!}\frac{1}{p^4} + \frac{D^8}{4!}\frac{1}{p^5} \ldots\ldots\right] \ldots\ldots\ldots (6)$$

The inverse Laplace transform of (6) provides

$$\theta(x) = c\left[1 + D^2x + \frac{D^4x^2}{2!\,2!} + \frac{D^6x^3}{3!\,3!} + \frac{D^8x^4}{4!\,4!} \ldots\right]$$

$$or \;\; \theta(x) = c\left[1 + \frac{1}{4}\left(2D\sqrt{x}\right)^2 + \frac{1}{2!2!}\left(\frac{2D\sqrt{x}}{2}\right)^4 + \frac{1}{3!3!}(\frac{2D\sqrt{x}}{2})^6 + \frac{1}{4!4!}(\frac{2D\sqrt{x}}{2})^8 \ldots\right] \ldots\ldots (7)$$

The modified Bessel function [5] of the first kind of order n and its first order derivative is given by

$$I_n(z) = \sum_{r=0}^{\infty}\frac{1}{r!(n+r)!}(\frac{z}{2})^{n+2r} \ldots\ldots\ldots (8)$$

$$\text{Also } \frac{d}{dx}\left(I_n(z)\right) = I_{n+1}(z)\frac{d}{dx}(z) \ldots. (9)$$

Put z = $2D\sqrt{x}$ and n = 0, we get

$$I_0\left(2D\sqrt{x}\right) = \sum_{r=0}^{\infty}\frac{1}{r!\,r!}(\frac{2D\sqrt{x}}{2})^{2r}$$

Or

$$I_0\left(2D\sqrt{x}\right) = 1 + \left(\frac{2D\sqrt{x}}{2}\right)^2 + \frac{1}{2!2!}(\frac{2D\sqrt{x}}{2})^4 + \frac{1}{3!3!}(\frac{2D\sqrt{x}}{2})^6 + \frac{1}{4!4!}(\frac{2D\sqrt{x}}{2})^8 \ldots\ldots$$

Hence (7) can be rewritten as

$$\theta(x) = cI_0\left(2D\sqrt{x}\right) \ldots. (10)$$

To find the constant c, at x = L, $\theta(L) = \theta_0$, [13] therefore, c = $\frac{\theta_0}{I_0(2D\sqrt{L})}$

Hence (10) can be written as

$$\theta(x) = \frac{\theta_0}{I_0(2D\sqrt{L})}I_0\left(2D\sqrt{x}\right) \ldots (11)$$

Equation (11) gives the temperature distribution along the length of the triangular fin.

The heat conducted through the triangular is given by Fourier's Law [6] of heat conduction as

$$H = kA\left(\theta'(x)\right)_{x=L} = kbt\left(\theta'(x)\right)_{x=L}$$

Using (11), we get

$$H = kbt\,\frac{\theta_0}{I_0(2D\sqrt{L})}I_1\left(2D\sqrt{L}\right)\left(\frac{d}{dx}\left(2D\sqrt{x}\right)\right)_{x=L}$$

On simplifying, we get

$$H = kbtD\,\frac{\theta_0}{\sqrt{L}\,I_0(2D\sqrt{L})}I_1\left(2D\sqrt{L}\right) \ldots. (12)$$

Put the value of D, we get

$$H = b\sqrt{2hkt}\,\frac{\theta_0}{I_0(2D\sqrt{l})}I_1\left(2D\sqrt{L}\right) \ldots\ldots (13)$$

Equation (13) gives the expression for the rate of conduction of heat through the triangular fin.

Case II: Parabolic fin

The differential equation for analyzing a parabolic fin [9] (assuming that heat flow pertains to one-dimensional conduction of heat) is given by

$$x^2\Theta''(x) + 2x\Theta'(x) - M^2l^2\Theta(x) = 0 \ldots\ldots (14),$$

$where\ M = \sqrt{\frac{2h}{tk}}$, l is the length of the fin between the base at x = l and the tip at x = 0, t is the thickness of the fin which increases uniformly from zero at the tip to t at the base, k is thermal conductivity, h is the coefficient of transfer of heat by convection, $\theta(x) = T(x) - T_s$ is the excess temperature, T_s is the temperature of the environment of the fin. Substituting $x = e^z$, the equation (14) can be rewritten into a form:

$$\theta''(x) + \theta'(x) - M^2l^2\theta(x) = 0 \ldots\ldots (15)$$

$$\theta' \equiv \frac{d}{dz}$$

The Laplace transform [10, 11] of (15) gives

$$[\,p^2\theta(p) - p\theta(0) - \theta'(0)] + p\,\theta(p) - \theta(0) - M^2l^2\theta(p) = 0 \ldots.. (16)$$

Put $\theta(0) = P\ and\ \theta'(0) = Q$, and by simplifying and rearranging (16), we get

$$\theta(p) = \frac{pP + Q}{p^2 + p - M^2l^2}$$

Or

$$\theta(p) = \frac{pP + Q}{(p - c_1)(p + c_2)} \ldots (17)$$

$where\ c_1 = \frac{-1+(1+4M^2l^2)^{1/2}}{2}\ and\ c_1 = \frac{-1-(1+4M^2l^2)^{1/2}}{2}$.

This equation (17) can be rewritten as

$$\theta(p) = \frac{c_1P + Q}{c_1 + c_2}\frac{1}{(p - c_1)} + \frac{c_2P + Q}{c_2 - c_1}\frac{1}{(p + c_2)} \ldots. (18)$$

The inverse Laplace transform [11] of (18) provides

$$\Theta(x) = \frac{c_1P + Q}{c_1 + c_2}\, e^{c_1z} + \frac{c_2P + Q}{c_2 - c_1} e^{-c_2z}$$

Or

$$\Theta(x) = \frac{c_1P+Q}{c_1+c_2}\, x^{c_1} + \frac{c_2P+Q}{c_2-c_1}x^{-c_2} \ldots. (19)$$

As $\Theta(0)\ is\ finite\ [1, 3], therefore,$
$the\ term\ \frac{c_2P+Q}{c_2-c_1}x^{-c_2}\ is\ equated\ to\ zero$

$$i.e. \frac{c_2P + Q}{c_2 - c_1}x^{-c_2} = 0, which\ gives$$

$$c_2P + Q = 0$$

or $Q = -c_2P$.

From (19), we have

$$\Theta(x) = \frac{c_1-c_2}{c_1+c_2} P\, x^{c_1} \ldots. (20)$$

To find the constant P, at x = l, $\Theta(l) = \Theta_0$, [12, 13] therefore, from (20), $P = \frac{c_1+c_2}{c_1-c_2}\Theta_0 l^{-c_1}$

Hence (20) can be rewritten as

$$\Theta(x) = \Theta_0 l^{-c_1} x^{c_1}$$

Or

$$\Theta(x) = \Theta_0 (x/l)^{c_1} \ldots (21)$$

Equation (21) gives the temperature distribution along the length of the parabolic fin.

The heat conducted through the parabolic fin is given by Fourier's Law of heat conduction [14, 15,] as

$$H = kA\left(\Theta'(x)\right)_{x=l} = kbt\left(\Theta'(x)\right)_{x=l}$$

Using equation (21), we get

$$H = kbt\,\Theta_0 c_1/l$$

Or

$$H = kbt\,\Theta_0 \frac{-1+(1+4M^2l^2)^{1/2}}{2l} \ldots.. (22)$$

Equation (22) gives the expression for the rate of conduction of heat through the parabolic fin.

III RESULTS AND CONCLUSION

We have found find the temperature distribution along the lengths of the triangular fin as well as the parabolic fin and hence the rate of conduction of heat through them via Laplace Transform means. It is found that with the increase in the length of the triangular fin or parabolic fin, temperature increases, and hence the rate of conduction of heat at any cross-section of the triangular fin or parabolic fin increases. The method has come out to be a very effective tool to find temperature distribution along the lengths of the triangular fin as well as parabolic fin and hence the rate of conduction of heat through them. It is clear that the results obtained are the same as obtained with other methods [1, 3, 6, 9, 12, 13,].

REFERENCES

[1] Dr. D.S. Kumar(2015), Heat and mass transfer. India, S.K. Kataria & Sons. 9th,Edition, Reprint, 2018.

[2]Rohit Gupta, Amit Pal Singh, Dinesh Verma, Flow of Heat Through A Plane Wall, And Through A Finite Fin Insulated At The Tip, International Journal Of Scientific & Technology Research,8(2019)125-128

[3] Gayatree Behura, Banamali Dalai, Analysis of Heat Transfer for the Varying Surface Fin, International Journal of Scientific and Engineering Research, 9(2018)80-85

[4] Murray R(1965) Spiegel, Theory and Problems of Laplace Transforms, Schaum's outline series, USA, McGraw - Hill.

[5] N.P. Bali and Dr. Manish Goyal(2014), A Text Book of Engineering Mathematics, India Laxmi Publications Pvt. Ltd; 9th edition

[6]Rohit Gupta, Neeraj Pandita, Dinesh Verma, Conduction Of Heat Through The Thin And Straight Triangular Fin, ASIO Journal of Engineering & Technological Perspective Research , 5(2020) 01-03 .

[7]Rohit Gupta, Rahul Gupta, Matrix method approach for the temperature distribution and heat flow along a conducting bar connected between two heat sources, Journal of Emerging Technologies and Innovative Research, 5(2018)210-214

[8]Rahul Gupta and Rohit Gupta, Laplace Transform method for obtaining the temperature distribution and the heat flow along a uniform conducting rod connected between two thermal reservoirs maintained at different temperatures‖, Pramana Research Journal, 8(2018) 47-54.

[9]Rohit Gupta, Neeraj Pandita, Rahul Gupta, Heat conducted through a parabolic fin via Means of Elzaki transform, Journal of Engineering Sciences, 11(2020) 533-535.

[10]Rahul Gupta, Rohit Gupta & Dinesh Verma, Laplace Transform Approach For The Heat Dissipation From An Infinite Fin Surface, Global Journal Of Engineering Science And Researches, 6(2019)6-101.
DOI- 10.5281/zenodo.2565939

[11]Rohit Gupta, Rahul Gupta, Sonica Rajput, Laplace Transforms Approach for the Velocity Distribution and Shear Stress Distribution of a Unidirectional Laminar Flow, International Journal for Research in Engineering Application & Management 4(2018)25-29.
DOI: 10.18231/2454-9150.2018.1149

[12]Rohit Gupta, Dinesh Verma, Heat Emitted From A Uniform Rod With Ends Maintained At Unequal Temperatures, ASIO Journal of Chemistry, Physics, Mathematics & Applied Sciences 4(2020)01-03.

[13] Rohit Gupta, Rahul Gupta, Heat Dissipation From The Finite Fin Surface Losing Heat At The Tip, International Journal of Research and Analytical Reviews, 5(2018)138-143.

[14]Neeraj Pandita, Rohit Gupta, Analysis Of Uniform Infinite Fin Via Means Of Rohit Transform, IJARIIE, 6(2020)1033-1036.

[15] Rahul Gupta, Rohit Gupta, Dinesh Verma, Determining Rate Of Heat Convected From A Uniform Infinite Fin Using Gupta Transform, Roots International Journal Of Multidisciplinary Researches, 7 (2021) 66-70.